

# 8515E Asphalt Paver

**LeeBoy**



Sleek, modern and low-profile are three words that immediately come to mind when evaluating the LeeBoy 8515E Asphalt Paver. Featuring an engine hood height of 69 inches (1.75 m) and a sliding control station, the 8515E gives the operator an extremely clear and comfortable view of their surroundings. With a class-leading tunnel size and self cleaning conveyor bars, this machine is built to perform at the highest level. Easy-to-access, convenient maintenance areas are also a highlight of machine ownership.

## Performance Features:

- 74 hp (48 kw) Kubota Tier 4 Final Diesel Engine
- Paving Widths Variable Up To 15' (4.5 m)
- Low Profile Engine Hood For Better Visibility
- Choice of High Deck or Low Deck Configuration
- Sliding Operator Control Station
- Ultra-efficient Material Management System
- Pressure Ports for Diagnostics and Testing
- 7.5 Ton (6,804 kg) Capacity Material Hopper
- Proven Legend Screed System
- Electric Screed Heat, 10 kw Generator
- Heavy-duty Undercarriage and Track System



# 8515E Asphalt Paver Specifications



Dimensions	<ul style="list-style-type: none"> <li>- Length: 13' 5" (4.08 m)</li> <li>- Width: 8' 6" (2.59 m) transport 10' (3.05 m) hopper wings down</li> <li>- Height: 8' (2.43 m)</li> <li>- Total Weight: 17,600 lbs. (7,983 kg)</li> </ul>	Steering	<ul style="list-style-type: none"> <li>- Dual electronic steering controls</li> <li>- Electronically controlled pumps operated by the forward/reverse joysticks</li> </ul>
Engine	Kubota turbocharged diesel, Tier 4 Final – 74 hp (55.4 kw)	Washdown System	Electric HD pump and two hose reels
Capacities	<ul style="list-style-type: none"> <li>- Fuel: 19 gallons (71 l)</li> <li>- Hydraulic reservoir: 67 gallons (254 l)</li> <li>- Washdown tank: 7 gallons (26 l)</li> </ul>	Push Rollers	Two vertically adjustable rollers with sealed bearings mounted to allow pivoting on frame
Hopper	Hopper size: 7.5 ton (6,804 kg)	Track Drive System	<ul style="list-style-type: none"> <li>- Hydrostatically powered, self-cleaning crawler type</li> <li>- Track size: 14" wide x 77" long (.36 x 1.95 m) steel</li> <li>- Paving speed: 0 to 150' per minute (1.7 mph)</li> <li>- Travel speed: 0 to 300' per minute (3.4 mph)</li> </ul>
Paving Widths	Variable up to 15' (4.6 m)	Additional Standard Equipment	<ul style="list-style-type: none"> <li>- Back-up alarm</li> <li>- Rotating LED safety beacon</li> <li>- LED working light package</li> <li>- Vandalism protection covers</li> <li>- Electronic gauge package (oil pressure, hour meter, fuel gauge, volt meter, water temp, tachometer, hydraulic oil temp, level warning)</li> </ul>
Paving Depths	<ul style="list-style-type: none"> <li>- Manual flight screws positioned on the screed to control material thickness</li> <li>- Depth: 0" to 6" (152 m)</li> </ul>	Optional Equipment	<ul style="list-style-type: none"> <li>- Legend Heavy-duty electric heated screed variable up to 15' (4.572 m), 10kw generator</li> <li>- Remote screed control</li> <li>- Automatic screed temperature controls</li> <li>- Screed extension vibration</li> <li>- Rubber track, continuous - in lieu of poly</li> <li>- Steel track – in lieu of poly</li> <li>- Sloping screed extensions</li> <li>- Heated end gates</li> <li>- Walkboard extensions slide outs (left and right)</li> <li>- Truck hitch</li> <li>- Power crown</li> <li>- Steering wheel drive controls (in lieu of joysticks)</li> <li>- Wiring only, grade controls, includes A/M module</li> <li>- Sonic grade control both sides</li> <li>- Sonic grade control, one side (TopCon)</li> <li>- Dual sonic grade (Topcon System P-32)</li> <li>- Dual sonic grade and slope (Topcon System P-32)</li> <li>- 12" x 4.5" (.3 x .11 m) berm extension, left and right</li> <li>- 4 – adjuster screed (special option)</li> <li>- Other options available</li> </ul>
Screed	<ul style="list-style-type: none"> <li>- Legend Electric screed</li> <li>- Consisting of a main screed and two hydraulically operated screed extensions</li> <li>- Equipped with two hydraulic vibrators</li> </ul>		
Screed Heat	<ul style="list-style-type: none"> <li>- Legend electric screed heat, 10kw generator</li> <li>- Electric timer and automatic RPM control system</li> <li>- 2 Blade heating elements in main, 1 blade element in each extension</li> </ul>		
Screed Crown/Valley	<ul style="list-style-type: none"> <li>- Equipped with a crown/invert adjustment</li> <li>- Includes a leveling indicator for the operator</li> </ul>		
Material Handling	<ul style="list-style-type: none"> <li>- Two independent hydraulically operated under auger material cutoffs</li> <li>- Two 12" (.305 m) independent hydraulically operated cast augers</li> </ul>		
Operator's Platform	Full machine width platform		
Operator's Controls	All control switches are in a single control box which can be moved from right side to left side		



ST Engineering LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300  
For additional products or information, visit our website: [www.LeeBoy.com](http://www.LeeBoy.com)

All trademarks identified by ® or ™ are registered trademarks of ST Engineering LeeBoy, Inc. The technical data contained herein is subject to change due to continuous engineering and product development. © 2019 ST Engineering LeeBoy, Inc. All rights reserved. BR-1008.8-EN

