

# 250 Tack Tank

**LeeBoy**



Perfect for the all-inclusive commercial paving contractor, the 250 Tack Distributor provides a perfectly sized tank for small to large projects including parking lots, patching, driveways or soil stabilization. Daily task can be completed with ease by relying on the trouble-free Honda powered engine and the proven reliable user-friendly design. Uniquely configurable, the customizable options give the contractor the ability to create a solution specific to their exact needs.

## Performance Features:

- 250 Gallon (946 l) Capacity Tank
- 4.8 hp (3.6 kw) Honda Engine
- 6' (1.8 m) Wand with On/Off Valve
- 40' (12.19 m) Heavy-Duty Recoil Hose Reel
- 4,500 lbs (2,041 kg) Loaded Weight
- Rear Tank Sampling Valve
- Two 54,000 BTU Propane Burners
- Trailer or Skid-Mount Configurations
- Electric brakes
- Emergency Brake-Away System
- Optional Accessories Available



# 250 Tack Distributor Specifications



Tank Size	250 gallons (946 l)
Dimensions (Trailer Configuration)	<ul style="list-style-type: none"> <li>- Length: 11' 6" (3.51 m)</li> <li>- Width: 6' 6" (1.98 m)</li> <li>- Height: 7' 6" (2.29 m)</li> <li>- Shipping Weight: 2,179 lbs (988.3 kg)</li> </ul>
Dimensions (Skid Mount Configuration)	<ul style="list-style-type: none"> <li>- Length: 6' 6" (1.98 m)</li> <li>- Width: 4' 4" (1.32 m)</li> <li>- Height: 5' 11" (1.8 m)</li> <li>- Shipping Weight: 1,380 lbs (626 kg)</li> </ul>
Engine	Honda – 4.8 hp (3.6 kw)
Capacities	- Fuel: 1 gallon (3.79 l)
Tank Dimensions	<ul style="list-style-type: none"> <li>- Length: 48.5" (1.23 m)</li> <li>- Width: 48.5" (1.23 m)</li> <li>- Height: 32.5" (.825 m)</li> </ul>
Asphalt Pump	- Specially designed 7 gallons per minute (26.5 lmp) pump
Heat System	<ul style="list-style-type: none"> <li>- Two 54,000 BTU propane burners</li> <li>- One start burner</li> <li>- 30 lbs (13.6 kg) propane fuel tank</li> </ul>
Temperature Gauge	- 50 - 300° F (10 - 149° C)
Flush Tank	- 7 gallons (26.5 l) tank with suck back valve

Hose and Reel	- .5" x 40' (13 mm x 12.19 m) heavy-duty recoil hose reel
Wand	<ul style="list-style-type: none"> <li>- 6' (1.829 m) wand with cold handles</li> <li>- On/off valve</li> <li>- Removable spray tip</li> </ul>
Fill Spout	10" x 10" (254 x 254 mm) with splash plate
Clean Out	- 4" (102 mm)
Access Valve	- 1" (25 mm)
Optional Equipment	<ul style="list-style-type: none"> <li>- Electric start (available on Honda-Gas and Hatz-Diesel engine)</li> <li>- 5 hp Hatz diesel engine (pull start)</li> <li>- Insulated tank</li> <li>- Auto ignition burners (only available with electric start engine)</li> <li>- Auto ignition burners with outfire protection (only available with electric start engines)</li> <li>- 8' (2.4 m) spray bar</li> <li>- Spray bar lift (only available on skid-mounted unit)</li> <li>- In-truck controls (requires 8' spray bar option)</li> <li>- Overnight heater</li> <li>- Surge brakes (only available on trailer mounted unit)</li> <li>- 2inch ball hitch</li> </ul>



ST Engineering LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300  
 For additional products or information, visit our website: [www.LeeBoy.com](http://www.LeeBoy.com)

All trademarks identified by ® or ™ are registered trademarks of ST Engineering LeeBoy, Inc. The technical data contained herein is subject to change due to continuous engineering and product development. © 2019 ST Engineering LeeBoy, Inc. All rights reserved. BR-4002.3-EN

