

# DS Water Truck

**Rosco**  
LeeBoy Group



Used in a multitude of applications including dust abatement, street cleaning and water transporting, the DS water truck has been engineered for long-lasting, strong performance. Contractors find the DS water truck to be an essential everyday staple in their operations due to its ability to fill complementary equipment such as rollers as well as to keep dust at manageable levels. This popular piece of equipment can also be found in rental fleets as a revenue generating solution that is easy-to-operate by any end user.

## Performance Features:

- Tank Capacities of 2,000, 3,000 or 4,000 Gallons
- 550 Gallons Per Minute (2,081 lpm)
- Direct PTO Drive from Truck Transmission
- Heavy-Duty Tank Construction
- Epoxy-lined Tank for Long Life
- Two Sprinkler Heads Mounted Horizontally at Truck Front
- Two Sprinkler heads Mounted Horizontally at Truck Rear
- One Midship Nozzle
- Versatile Truck for Various Applications



# DS Water Truck Specifications



Tank Capacity	<ul style="list-style-type: none"> <li>- 2,000 gallons (7,571 l)</li> <li>- 3,000 gallons (11,356 l)</li> <li>- 4,000 gallons (15,142 l)</li> </ul>	Additional Standard Equipment	<ul style="list-style-type: none"> <li>- ICC clearance lights and reflectors, meet federal motor vehicle safety standard 108</li> <li>- Full width fender, mud flaps</li> <li>- Ladder over fender for access to tank opening</li> <li>- Hose hooks</li> <li>- Rear bumper</li> <li>- Backup alarm</li> <li>- .75" (19 mm) pressurized hose outlet</li> </ul>
Tank	<ul style="list-style-type: none"> <li>- Elliptical steel with flat, flanged reinforced heads</li> <li>- Full section 7 gauge (4.76 mm) surge plates</li> <li>- Air gap fill on tank top</li> <li>- Interior sandblasted and coated with epoxy</li> <li>- Top opening: 22" (.559 m)</li> <li>- Air gap: 6" (153 mm) with hose</li> </ul>	Optional Equipment	<ul style="list-style-type: none"> <li>- Installation for a customer supplied truck chassis</li> <li>- 8' (2.43 m) spraybar</li> <li>- Suction filling attachment, including primer pump and foot valve strainer</li> <li>- 2.5" (63.5 mm) fire fighting valve</li> <li>- Push bumper</li> <li>- Hose reel, rear-mounted manual rewind</li> <li>- Hose reel, rear mounted electric rewind</li> <li>- 2" (51 mm) brass flusher nozzles (in lieu of sprinkler caps)</li> <li>- Water canon with cab control</li> </ul>
Pump	<ul style="list-style-type: none"> <li>- Single stage, Berkley centrifugal water pump</li> <li>- Rated at 550 gpm (2,081 lpm) @55 psi turning 2,200 rpm</li> </ul>		
Pump Drive	<ul style="list-style-type: none"> <li>- Direct PTO drive from truck transmission</li> <li>- Shifting control in truck cab</li> </ul>		
Sprinkler Heads	<ul style="list-style-type: none"> <li>- Two sprinkler heads mounted horizontally at front of truck</li> <li>- Two sprinkler heads mounted horizontally at the rear of truck</li> <li>- One midship nozzle</li> <li>- Electric solenoid controlled water valve</li> </ul>		



VT LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300  
 For additional products or information, visit our website: [www.LeeBoy.com](http://www.LeeBoy.com)



BR-1301.0-EN This document contains information applicable for the U.S. and U.S. Territories. For International product availability, specifications and support, please contact your authorized LeeBoy representative. The technical data contained herein is subject to change due to continuous engineering and development. Accordingly, LeeBoy Group reserves the right to modify at any time.