

8530 Asphalt Paver

LeeBoy®



Performance Features:

We've set the standards in heavy-commercial paving even higher! Equipped with exciting new features that were truly designed with the paving professional in mind, the LeeBoy 8530 is a 125hp workhorse. Standard machine assets include the 4,150 lbs Legend HD PRO Screed with spring-loaded end gates, front adjustable heavy-duty conveyor chains, pivoting dual seating and controls, a LeeBoy 2-year product warranty as well as many other enhancements. As always, LeeBoy's wide slow-moving conveyor system moves material from the truck to the screed without segregation which ensures a flawless mat.

- 125 hp (93 kw) Kubota Tier 4 Final Diesel Engine
- Legend HD PRO Screed, Weight 4,150 lbs
- Paving Widths Variable Up To 15' 6"
- 9 Ton Capacity Material Hopper
- Operator's Choice of High or Low Deck Configuration
- Remote Mounted SCR for Greater Visibility
- Dual Electronic Steering & Adjustable Operator Platforms
- Ultra-efficient Wide-Conveyor Material Management
- Automatic Temperature Control (ATC) Standard
- Electric Screed Heat, 14.4 kw Generator
- Actuator Driven Hood Lift to Aid in Maintenance



8530 Asphalt Paver Specifications



Dimensions	<ul style="list-style-type: none"> - Length: 15' - Width: 8' 6" transport 10' hopper wings down - Height: Low Deck: 6' 8" High Deck: 7' 9" - Total Weight: 22,520 lbs. 	Operator's Controls	<ul style="list-style-type: none"> - Dual adjustable, independent control stations - Colored LED, sunlight viewable control screens with digital readouts
Engine	<ul style="list-style-type: none"> - Kubota turbocharged diesel, Tier 4 Final – 125 hp (93.2 kw) 	Steering	<ul style="list-style-type: none"> - Dual electronic steering controls - Electronically controlled pumps operated by the forward/reverse joysticks
Capacities	<ul style="list-style-type: none"> - Fuel: 32 gallons - Hydraulic reservoir: 25 gallons - Washdown tank: 7 gallons - DEF tank: 5 gallons 	Washdown System	<ul style="list-style-type: none"> - Electric HD pump with hose and two hose reels
Hopper	<ul style="list-style-type: none"> - Hopper size: 9 ton 	Push Rollers	<ul style="list-style-type: none"> - Two rollers with sealed bearings mounted to allow pivoting on frame, built in material scrapers - Vertically adjustable oscillating push rollers
Paving Widths	<ul style="list-style-type: none"> - Variable up to 15' 6" 	Track Drive System	<ul style="list-style-type: none"> - Hydrostatically powered, self-cleaning crawler type - Track size: 14" w x 87" l poly - Paving speed: 0 to 150' per minute (1.7 mph) - Travel speed: 0 to 300' per minute (3.4 mph)
Paving Depths	<ul style="list-style-type: none"> - Manual flight screws positioned on the screed to control material thickness, depth: 0" to 8" 	Additional Standard Equipment	<ul style="list-style-type: none"> - Gauge package - Actuator-driven hood lift - LED beacon light - LED work light package - Integrated tool boxes - Vandalism protection covers - 2 Year Standard Product Warranty
Screed	<ul style="list-style-type: none"> - Legend HD PRO Screed, free floating - Weight: 4,150 lbs - Consisting of a main screed and two hydraulically operated screed extensions - Spring-loaded end gates standard - Sloping screed extensions standard - Equipped with two electric vibrators, 4100 RPM 	Optional Equipment	<ul style="list-style-type: none"> - Additional control post, wire harness - left side - Screed extension vibration - Rubber track, continuous - Heated end gates - Slope meter - Horizontal flight screw - 3:1 flight screw adjusters - Truck hitch - Power crown - Hydraulically extendable oscillating push roller - Central point lube system - Steering knob drive controls, in lieu of joysticks - Wiring only, grade controls (TopCon) - Sonic grade control, one side (TopCon) - Dual grade control (TopCon) - Dual grade and slope (TopCon) - 12" x 6" berm extensions, left and right - Other options available, visit LeeBoy.com
Screed Heat	<ul style="list-style-type: none"> - Legend electric screed heat, 14.4 kw generator - Electric timer and automatic temperature control - Sealed s-curve elements in main screed and sealed blade-style elements in extensions 		
Screed Crown/Valley	<ul style="list-style-type: none"> - Equipped with a crown/invert adjustment - Includes a levelling indicator for the operator 		
Material Handling	<ul style="list-style-type: none"> - Two hydraulically operated under auger material cutoffs can close in reverse - Single point lube system - Two 12" independent hydraulically operated cast augers 		
Operator's Platform	<ul style="list-style-type: none"> - Full machine width platform, slide out extensions - Pivoting, swing out seats and control panels 		



ST Engineering LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300
www.LeeBoy.com



LeeBoy and the LeeBoy logo are registered trademarks of ST Engineering LeeBoy, Inc. Equipment model names, slogans and subsidiary logos appearing in this collateral may be registered trademarks or the trademarks of ST Engineering LeeBoy, Inc. The technical data contained herein is subject to change due to continuous engineering and development. Accordingly, LeeBoy reserves the right to modify at any time. © 2020 ST Engineering LeeBoy, Inc. All rights reserved. BR-1012.4-EN