

Challenger 7 Self Propelled Broom

Rosco
A LeeBoy Company



The Challenger 7 front-mounted broom exhibits all of the high-end features you could expect from a self propelled broom. Serving as a pleasurable amenity, the quick-change core system allows the brush to be changed swiftly with no tools required. Ergonomic joystick controls provide simple-to-use travel and broom functions while also granting a 3 foot turning radius for the ultimate maneuverability. In addition to an extra-heavy duty frame, the Challenger 7 features a high-raise lift to ensure easy trailer loading and unloading.

Performance Features:

- 74 hp (55 kw) Cummins Tier 4 Final Diesel Engine
- 7,500 lbs (3,401 kg) weight
- Choice of 7' 6" (2.28 m) or 8' (2.43 m) Heavy-Duty Frame with Poly-Steel Tube Brush
- 150 gallons (568 l) Rear-Mounted Brush Watering System
- Joystick Control for Travel and Broom Functions
- Hydrostatic Drive
- Rear Steering for 3' (.91 m) Turning Radius
- Variable Brush Down-Pressure and Brush Speed Control
- Single Door ROPS Climate-Controlled Cab



Challenger 7 Broom Specifications



Dimensions	<ul style="list-style-type: none"> - Length: 18' 6" (5.63 m) with water 15' 3" (4.64 m) without water - Width: 8' 6" (2.59 m) not tilted - Height: 9' 5" (2.87 m) with beacon - Wheelbase: 5' 5" (1.65 m) - Turning Radius: 3' (.91 m) - Total Weight: 7,500 lbs. (3,401 kg) w/ water
Engine	Cummins turbocharged diesel, Tier 4 Final – 74 hp (55 kw)
Capacities	<ul style="list-style-type: none"> - Fuel: 35 gallons (132 l) - Hydraulic reservoir: 24 gallons (91 l)
Transmission	<ul style="list-style-type: none"> - Hydrostatic drive - Speed infinitely variable, 0 to 15 mph (24 kph)
Front Axle	<ul style="list-style-type: none"> - Heavy-duty, limited slip differential - Tires: 8.75 x 15 in, load range E, highway tread - Rim: 4 steel disc type, 15 x 6.57 in
Rear Axle	- Heavy-duty truck type, oscillating
Brakes	<ul style="list-style-type: none"> - Dynamic braking with two wheel drive axle disc type brakes in oil bath - Hand operated parking brake - Foot operated de-stroke breaking of the hydrostatic drive
Hydraulic System	- Two separate circuits, one for travel, one for brush control and power steering
Main Frame	- .75 x 12" (19 x 305 mm) plate steel and 2" x 6" (51 x 152 mm) rectangular A 500 tubing with .25" (6 mm) wall thickness
Instrumentation	<ul style="list-style-type: none"> - PV 101 digital display includes: oil pressure, water temperature, voltmeter, tachometer, hour meter - Fuel gauge

Brush	<ul style="list-style-type: none"> - Joystick control of swing and up/float motions - Variable down pressure, brush rotation, speed control - Quick change design allows operator to change out brush quickly without tools - Driven hydraulic by separate pump and heavy duty motor, independent of propulsion circuit
Brush Frame Choices	<ul style="list-style-type: none"> - 7' 6" (2.28 m) heavy-duty frame with poly-steel tube brush, 32" (.81 m) diameter, 7' 6" (2.28 m) long, sweep angle: 35° left or right, variable speed 0 to 180 rpm, brush frame is welded, heavy gauge steel - 8' (2.43 m) heavy-duty frame with poly-steel tube brush, 32" (.81 m) diameter, 8' (2.43 m) long, sweep angle: 35° left or right, variable speed 0 to 180 rpm, brush frame is welded, heavy gauge steel
Additional Standard	<ul style="list-style-type: none"> - Fully enclosed ROPS cab with air conditioner, heater and defroster - Seat with safety belt, horn, dual west coast style mirrors and dome light - Tinted safety glass - Rear-mounted brush watering system, 150 gallon tank (568 l) with brush spraybar, electric pump and filter - Two LED head lights, stop, turn, tail, rear working lights and amber strobe light - Back-up alarm - Toolbox
Optional Equipment	<ul style="list-style-type: none"> - Cab air filtration and pressure monitor system (MERV 16 rated) - 8' heavy-duty frame, poly/steel tube brush - Combination poly wafers or poly/steel wafers - Rear wiper and washer assembly - Front windshield washer, wiper is standard - Suspension seat assembly w/ safety belt - Back up/reverse camera w. in-cab color display - Radio/CD/Bluetooth w/ dual speakers & remote - Cold weather package, block heater - Additional options available, visit LeeBoy.com



ST Engineering LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300
www.LeeBoy.com

LeeBoy and the LeeBoy logo are registered trademarks of ST Engineering LeeBoy, Inc. Equipment model names, slogans and subsidiary logos appearing in this collateral may be registered trademarks or the trademarks of ST Engineering LeeBoy, Inc. The technical data contained herein is subject to change due to continuous engineering and development. Accordingly, LeeBoy reserves the right to modify at any time. © 2020 ST Engineering LeeBoy, Inc. All rights reserved. BR-1101.6-EN

